

#### PUMP MAINTENANCE SCHEDULE AND CHECKLISTS

Providing a maintenance schedule defined specifically by run hours or yardage pumped serves only as a general guideline given the large amount of variables a unit might be subject to, such as weather and ambient temperature conditions, jobsite conditions, material differences of concrete mix design, the load burden the unit is typically subject to, i.e. light, medium or heavy duty operation, etc.

The list that follows is to be used as a reference guide. However, the end user is encouraged to develop a preventative maintenance program that specifically suites their needs depending on the usage of the equipment.

DAILY PUMP MAINTENANCE CHECKLIST		
Actual Hours Date_/		/
#	Maintenance Description	Initials
1	Check hydraulic tank fluid levels	
2	Check condition of hydraulic oil for water or other contamination.	
3	Drain water from hydraulic tank	
4	Check flush box fluid levels	
	NOTE: If water is used instead of oil, water should be drained DAILY	
5	Check engine fluid levels (see engine manufacturer maintenance schedule for additional requirements)	
	Additional Notes:	
6	Check hydraulic filter indicator condition	
7	Lubricate lubrication points, during and after pumping	
8	Inspect unit for fluid leaks, loose hoses, loose nuts, bolts, fasteners etc.	
	Additional Notes:	
9	Trailer Towing Safety Inspection	
	a) brakes functional	
	b) air pressure in tires is adequate and tire condition	
	c) all "lug nuts" are secure and in place	
	d) tow hitch is secure and in good condition	
10	Additional Notes:	



INITIAL 50 HOUR MAINTENANCE CHECKLIST			
Actual Hours Date_/_		/	
#	Maintenance Description	Initials	
1	Change engine oil and filters (see engine manufacturer maintenance schedule for additional requirements)		
	Additional Notes:		
2	Change hydraulic oil filters		
3	Inspect hydraulic hoses and fittings for any signs of external wear or damage		
	Additional Notes:		



EVERY 100 HOUR MAINTENANCE CHECKLIST			
Actual Hours Date_ /			
#	Maintenance Description	Initials	
1	Clean hydraulic tank breather		
2	Inspect all structural components (check frame, hopper, axle, hood, towing		
	hook, and other structural members for any damage)		
	Additional Notes:		
3	Adjust "S-Tube Nut" or "Castle Nut" (refer to "S-Tube Adjustment" in		
	Maintenance Section)		
	Additional Notes:		
4	Change flush box oil and examine for excessive amounts of contamination		
	(excessive contamination might indicate need to change the Piston Cups)		
	Additional Notes:		
5	Check coolers and radiators for dirt or debris. Clean as necessary		
5	Check coolers and radiators for dirt of debris. Clean as necessary		
6	Check condition of engine drive belts. Change if necessary (see engine		
Ŭ	manufacturer maintenance schedule for additional requirements)		
۸dd	itional Notes:		
Add	lional notes.		



EVERY 250 HOUR MAINTENANCE CHECKLIST			
Actual Hours Date_/_/			
#	Maintenance Description	Initials	
1	Change hydraulic filters (or change more frequently as indicated by indicator gauge on filter)		
2	Check that S-Tube, wear parts and seals in hopper are secure and adjusted well, rotate wear ring and replace seal if necessary		
	Additional Notes:		
3	Check swing cylinder components: cylinders, bell crank, pins, bushings, bearings and grease fittings are secure, tight, and not worn excessively		
	Additional Notes:		
4	Check piston cup wear (as indicated by analysis of contaminants found in flush box oil)		
	Additional Notes:		
5	Check that all electrical wires, cables, terminals, plugs are in good condition		
	Additional Notes:		
6	Change engine oil and filters (see engine manufacturer guide for all engine requirements)		
	Additional Notes:		
7	Check condition of fuel hoses, fittings, and clamps		
	Additional Notes:		
8	Inspect all safety decals to ensure that they are completely visible and legible		



EVERY 250 HOUR MAINTENANCE CHECKLIST			
Actual Hours Date/_		/ <u>/</u>	
#	Maintenance Description	Initials	
9	Perform complete inspection of the controls		
10	All toggles in good condition, stay in position or momentarily return to center		
11	Control identification in good condition, legible		
12	Gauges in good condition		
	Additional Notes:		
13	Remote controls, control console in good condition		
14	Switch in good condition		
15	Cord in good condition, no cuts, securely mounted to box		
	Additional Notes:		
16	Trailer frame integrity, visually check welds, cracks		
17	Torsion axle secure		
18	Wheels and tires, lug nuts tight, tire inflation		
19	Electric brakes, breakaway switch connected		
20	Front jack stand handle turns easily, smoothly		
21	Manual jacks slide freely, lock pins in place		
22	Lighting good condition operational		
Add	Additional Notes:		



EVERY 500 HOUR MAINTENANCE CHECKLIST		
Act	ctual Hours Date_/_/	
#	Maintenance Description	Initials
1	Inspect hydraulic hoses and fittings for any signs of external wear or damage	
	Additional Notes:	
2	Inspect all wear parts and change as necessary (excessive wear may cause	
	inefficient performance and/or shutdown of operation)	
	Additional Notes:	
3	Change hydraulic fluid, clean the reservoir and the suction strainers within reservoir, and replace all hydraulic oil filters	
	A Series requires 51 gallons when system is empty, 45 if filling tank only.	
	B Series requires 58 gallons when system is empty, 51 if filling tank only.	
	C Series requires 65 gallons when system is empty, 57 if filling tank only.	
	Additional Notes:	
4	Complete inspection of the engine (refer to engine manufacturer maintenance	
	schedule for details)	
5	Inspect mountings, bolts, brackets	
6	Oil level proper, coolant level proper, check for leaks	
7	Fuel system, tank mounting, filter condition, check for leaks, damaged lines	
8	Battery hold down, condition, tightness of cables	
9	Key switch, indicator lights operable	
10	Throttle control functional	
11	Air cleaner and muffler securely mounted	
Add	itional Notes:	



13822 Oaks Avenue Chino, CA 91710 reedpumps.com (909) 287 - 2100

EVERY 500 HOUR MAINTENANCE CHECKLIST			
Actual Hours Date _/		_//	
#	Maintenance Description	Initials	
12	Pump cell check for structural damage, cracked welds		
13	Hydraulic drive cylinders in good condition, secure, check for leaks		
14	Material cylinders secure, tie rods tight		
15	Water box structurally sound, clean, cover in place		
16	S-Tube shift mechanism structurally sound, all pins and retainers in place		
17	Hydraulic shift cylinders in good condition		
18	Bearing housing, seals etc. in good condition		
19	Hydraulic hoses secure no leaks		
	Additional Notes:		
20	Hopper check for structural damage, cracked welds		
21	S-Tube secure, in good condition		
22	Check condition of wear plate, wear ring, seals		
23	Check connection of S-Tube to outlet, seals, bearing		
24	Hopper drain is functional		
Add	itional Notes:		



13822 Oaks Avenue Chino, CA 91710 reedpumps.com (909) 287 - 2100

EVERY 500 HOUR MAINTENANCE CHECKLIST			
Actual Hours	Date	/	/
ADDITIONAL GENERAL NOTES:			